



Wall mounted unit

FTXB-C - INVERTER



INVERTER



Econo mode



Energy saving during standby mode



Comfort mode



Vertical auto swing

Wall mounted unit for low energy consumption and pleasant comfort

- Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.

- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- 24 hour timer can be set to start heating or cooling anytime during a 24 hour period

FTXB-C + RXB-C



Indoor unit		FTXB	25C	35C	50C	60C
Casing	Colour		White			
Dimensions	Unit	HeightxWidthxDepth	283x770x216		310x1,065x224	
Sound power level	Cooling/Heating	dBA	55/55	58/58	55	61
	Cooling	Super High/High/Nom./Low/Silent operation	-/40/33/26/21	-/41/34/27/23	44/40/38/35/32	46/43/41/37/33
Sound pressure level	Cooling	Super High/High/Nom./Low/Silent operation	-/40/34/28/25	-/41/35/29/26	44/40/38/35/32	46/43/41/37/33
	Heating	Super High/High/Nom./Low/Silent operation				
Control systems	Infrared remote control		ARC470A1			


Efficiency data		FTXB + RXB	25C + 25C	35C + 35C	50C + 50C	60C + 60C	
Cooling capacity	Min./Nom./Max.	kW	1.3/2.5/3.0	1.3/3.3/3.8	1.630/5.480/6.200	1.750/6.230/6.500	
	Min./Nom./Max.	kW	1.3/2.8/4.0	1.3/3.5/4.8	1.170/5.620/6.600	1.200/6.400/7.100	
Heating capacity	Min./Nom./Max.	kW	0.310/0.770/1.050	0.290/1.030/1.300	0.280/1.700/1.910	0.280/1.931/2.000	
	Min./Nom./Max.	kW	0.250/0.700/1.110	0.290/0.940/1.290	0.240/1.500/1.880	0.240/1.680/2.000	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A+				
		Pdesign	kW	2.50	3.30	5.48	6.23
		SEER		6.02	6.05	5.93	6.09
	Annual energy consumption	kWh	145	191	324	359	
	Heating (Average climate)	Energy label	A+				
Pdesign		kW	2.40	2.80	3.64	3.80	
SCOP			4.01	4.06	4.27	4.06	
Nominal efficiency	EER		838	966	1,195	1,311	
		Annual energy consumption	kWh	3.25	3.21	3.22	3.23
	COP		4.01	3.71	3.75	3.81	
		Annual energy consumption	kWh	385	514	851	964
Energy label	Cooling/Heating	A/A					

Outdoor unit		RXB	25C	35C	50C	60C
Dimensions	Unit	HeightxWidthxDepth	550x658x275		753x855x328	
Sound power level	Cooling	dBA	60	62	64	65
	Heating	dBA	61	62	64	65
Sound pressure level	Cooling	High/Nom.	46/-	48/-		-/51
	Heating	High/Nom.	47/-	48/-		-/51
Operation range	Cooling	Ambient Min.-Max.	-10-46			
	Heating	Ambient Min.-Max.	-15-18			
Refrigerant	Type/GWP		R-410A/2,087.5			
	Charge	kg	0.74/1.5	1.0/2.1	1.45/3.0	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240			

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35/27° nominal load, heating at 7/20° nominal load
Contains fluorinated greenhouse gases



Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-027 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF). Check ongoing validity of certificate online: www.eurovent-certification.com or using www.certifiah.com

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.