

1. Combination Table

Online Air Conditioning Store

1-2. AJ050MCJ2EH/TK

COOLING

Unit	Indoor Index					Cooling Capacity [W]					Capacity			Power Consumption			Current			Effic. STD. Cooling. At 35 °C / 27 °C	SEASONAL EFFICIENCY (ACCORDING EN14825)		Qce
	A	B	C	D	E	A	B	C	D	E	W			W			A						
											MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX				
2	7	7				2000	2000				1300	4000	4800	350	1245	1490	1.9	5.7	6.8	3.21	A+	6.07	231
	7	9				2040	2560				1300	4600	5200	350	1430	1720	1.9	6.5	7.9	3.22	A+	6.08	265
	7	12				1820	3180				1400	5000	5400	350	1490	1780	1.9	6.8	8.1	3.36	A++	6.11	287
	7	18				1430	3570				1400	5000	5400	350	1450	1800	1.9	6.6	8.2	3.45	A++	6.13	286
	9	9				2500	2500				1400	5000	5400	350	1500	1780	1.9	6.9	8.1	3.33	A++	6.40	274
	9	12				2080	2920				1400	5000	5400	350	1500	1780	1.9	6.9	8.1	3.33	A++	6.29	278
	9	18				1670	3330				1400	5000	5400	350	1450	1700	1.9	6.6	7.8	3.45	A++	6.23	281
	12	12				2500	2500				1400	5000	5400	350	1500	1780	1.9	6.9	8.1	3.33	A++	6.10	287
	12	18				2060	2940				1400	5000	5400	350	1320	1700	1.9	6.0	7.8	3.79	A++	6.30	278

HEATING

Unit	Indoor Index					Heating Capacity [W]					Capacity			Power Consumption			Current			Effic. STD. Heating. At 7°C / 20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)				Qhe
	A	B	C	D	E	A	B	C	D	E	W			W			A								
											MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX						
2	7	7				2200	2200				1100	4400	4750	280	1220	1390	1.4	5.6	6.4	3.61	A+	4.00	3.05	1068	
	7	9				2040	3060				1100	5100	5460	280	1410	1610	1.4	6.5	7.4	3.62	A+	4.00	4.21	1471	
	7	12				2020	3680				1100	5700	6300	280	1520	1900	1.4	7.0	8.7	3.75	A+	4.00	4.21	1471	
	7	18				1530	4170				1100	5700	6400	280	1440	1800	1.4	6.6	8.2	3.96	A	3.86	4.07	1478	
	9	9				2850	2850				1100	5700	6300	208	1550	1940	1.4	7.1	8.9	3.68	A+	4.01	4.21	1467	
	9	12				2580	3120				1100	5700	6300	280	1550	1850	1.4	7.1	8.5	3.68	A+	4.01	4.21	1470	
	9	18				2020	3680				1100	5700	6400	280	1440	1750	1.4	6.6	8.0	3.96	A	3.86	4.07	1478	
	12	12				2850	2850				1100	5700	6300	280	1470	1840	1.4	6.7	8.4	3.88	A	3.86	4.07	1478	
	12	18				2280	3420				1100	5700	6400	280	1350	1750	1.4	6.2	8.0	4.22	A	3.86	4.07	1478	

NOTE

- EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- The above is the value for connecting with the following indoor units.
 - A3050 Better : AJ020/025/035/050×BAPEH/TK
- You can not connect a single unit.
- Power consumption include indoor unit power.