



Series 2, Wall-mounted Extractor Hood, 90 cm, clear glass black printed DWK095G60







The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- **LED-Illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- Extraction rate: at MAX_FOERDERLEISTUNG m3/h, it quickly ensures optimal kitchen air quality.
- Metal grease filters: filter grease and other solid particles out of the extracted air
- Pi shaped double metal filter
- TouchControl control at your fingertips.

Technical data

Typology: Wall-mounted

Length electrical supply cord : 130 cm Height of product, without chimney : 354 mm

Net weight: 15.5 kg Type of control: Electronic Number of speed settings: 3

Maximum output air extraction : 629 m³/h Maximum output recirculating air : 230 m³/h

Number of lights: 2

Noise level: 67 dB(A) re 1 pW Diameter of air outlet: 150 / 120 mm Grease filter material: Washable aluminium

Odour filter : No

Operating Mode : Convertible Optional accessories : DWA0LK6A

Type of lamps used: LED
Grease filter type: Kassette
Connection Rating: 216 W
Fuse protection: 10 A
Voltage: 220-240 V
Frequency: 50 Hz

Plug type: Gardy plug w/ earthing Installation typology: Wall-mounted Material body: Glass, Lacquered Plug type: Gardy plug w/ earthing

Dimensions of the product, with chimney (if exists) (in) : / x x Dimensions of the packed product : $18.11 \times 38.58 \times 18.89$

Net weight : 34.000 lbs Gross weight : 44.000 lbs

Motor location: Integrated motor in hood body

No-return airflow flap: Yes

Length electrical supply $cord:130\ cm$

Dimensions of the product, with chimney (if exists) : x 896.0 x

386.0 mm

Dimensions of the packed product (HxWxD): 460 x 980 x 480

mm

Net weight : 15.5 kg Gross weight : 20.0 kg




Series 2, Wall-mounted Extractor Hood, 90 cm, clear glass black printed DWK095G60

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.


- Chimney extractor hood
- Designed for wall mounted installation
- Suitable for ducted or recirculating operation
- 90 cm wide
- Recirculating kit
- touch control with Electronic display
- Electronic controls via touch control with Electronic display
- black with glass canopy
- 3 speed operation
- Metal grease filter with side extraction
- Filter cover glass
- Removable metal grease filters, dishwasher safe
- Maximum extraction 629 m3/h
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Power rating: 216 W
- Light Intensity: 377 lux
- Colour Temperature: 3000 K
- Energy Efficiency Class: C*
- Average Energy Consumption: 94.5 kWh/year*
- Noise max. Normal Level: 67 dB*





Series 2, Wall-mounted Extractor Hood, 90 cm, clear glass black printed DWK095G60



measurements in mm







Exhaust air (2) Circulated air
 Air outlet – slots for exhaust air to be mounted facing down measurements in mm



Online Store