

Series 2, Wall-mounted Extractor Hood, 90 cm, Stainless steel DWP94CC50M



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- **silent:** maximal extractor performance with little noise
- **Extraction rate:** at MAX_FOERDERLEISTUNG m³/h, it quickly ensures optimal kitchen air quality.
- **Metal grease filters:** filter grease and other solid particles out of the extracted air
- Pi shaped double metal filter

Technical data

Typology : Wall-mounted
 Length electrical supply cord : 120 cm
 Height of the chimney : 410-765/410-765 mm
 Height of product, without chimney : 250 mm
 Net weight : 13.7 kg
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction : 380 m³/h
 Maximum output recirculating air : 235 m³/h
 Number of lights : 2
 Noise level : 64 dB(A) re 1 pW
 Diameter of air outlet : 150 mm
 Grease filter material : Washable aluminium
 Odour filter : No
 Operating Mode : Convertible
 Optional accessories : DWA0KP6A, DWZ6HP1U2
 Type of lamps used : LED
 Total power of the lamps : 10 W
 Grease filter type : Kasette
 Connection Rating : 135 W
 Voltage : 220-240 V
 Frequency : 50 Hz
 Plug type : GB plug
 Installation typology : Wall-mounted
 Material body : Stainless steel
 Plug type : GB plug
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product : 15.74 x 39.76 x 22.83
 Net weight : 30.000 lbs
 Gross weight : 34.000 lbs
 Motor location : Integrated motor in hood body
 No-return airflow flap : No
 Length electrical supply cord : 120 cm
 Dimensions of the product, with chimney (if exists) : 790-1015 x 898.0 x 470.0 mm
 Dimensions of the packed product (HxWxD) : 400 x 1010 x 580 mm
 Net weight : 13.7 kg
 Gross weight : 15.4 kg

Series 2, Wall-mounted Extractor Hood, 90 cm, Stainless steel DWP94CC50M

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- DWP94CC50M
- 90 cm, Chimney extractor hood

Design:

- Brushed steel
- Designed for wall mounted installation

Comfort and Safety:

- Energy Efficiency Class: D*
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 72.8 kWh/year*

Comfort:

- push buttons for extractor speeds and light
- Removable metal grease filters, dishwasher safe

Operating and power:

- Suitable for ducted or re-circulated extraction
- 3 speed operation
- Power rating: 135 W

Measures:

- 150 mm diameter pipe
- Ducted extraction rate according to DIN/EN 61591 max. 380 m³/h
- Dimensions exhaust air (HxWxD): 790-1015 x 898 x 470 mm
- Dimensions recirculating (HxWxD): 790-1015 x 898 x 470 mm
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW (50 dB(A) re 20 µPa sound pressure)
- Noise max. Normal Level: 64 dB*
- Light Intensity: 1000 lux
- Colour Temperature: 4000 K

** In accordance with the EU-Regulation No 65/2014*

**Series 2, Wall-mounted Extractor Hood, 90
cm, Stainless steel
DWP94CC50M**

