

iQ100, Wall-mounted Extractor Hood, 90 cm, clear glass black printed LC95KA670



The wall-mounted chimney hood with high extraction rate – perfect for installing on the kitchen wall.

✓ LED light: For optimal visibility and atmosphere when cooking.

Features

Technical data

Typology : Wall-mounted
 Length electrical supply cord : 130 cm
 Height of product, without chimney : 354 mm
 Net weight : 15.5 kg
 Type of control : Electronic
 Number of speed settings : 3
 Maximum output air extraction : 629 m³/h
 Maximum output recirculating air : 230 m³/h
 Number of lights : 2
 Noise level : 67 dB(A) re 1 pW
 Diameter of air outlet : 150 / 120 mm
 Grease filter material : Washable aluminium
 Odour filter : No
 Operating Mode : Convertible
 Optional accessories : LA10LKA6
 Type of lamps used : LED
 Grease filter type : Kassette
 Connection Rating : 216 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50 Hz
 Plug type : Gardy plug w/ earthing
 Installation typology : Wall-mounted
 Material body : Glass, Lacquered
 Plug type : Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product : 18.11 x 38.58 x 18.89
 Net weight : 34.000 lbs
 Gross weight : 44.000 lbs
 Motor location : Integrated motor in hood body
 No-return airflow flap : Yes
 Length electrical supply cord : 130 cm
 Dimensions of the product, with chimney (if exists) : x 896.0 x 386.0 mm
 Dimensions of the packed product (HxWxD) : 460 x 980 x 480 mm
 Net weight : 15.5 kg
 Gross weight : 20.0 kg

iQ100, Wall-mounted Extractor Hood, 90 cm, clear glass black printed LC95KA670

Features

Design:

Operating and power:

Power:

Comfort and Safety:

Comfort:

Measures:

Technical information:

- Energy Efficiency Class: C*
- Average Energy Consumption: 94.5 kWh/year*
- Blower Efficiency Class: D*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Noise max. Normal Level: 67 dB*
- 90 cm black Chimney hood with glass canopy
- black with glass canopy
- Glass plate clear glass black printed
- Suitable for ducted extraction and recirculation
- Recirculating kit
- Designed for wall mounted installation
- touch control with Electronic display
- 3 speed control
- Light Intensity: 377 lux
- Colour Temperature: 3000 K
- Metal grease filter with side extraction
- Filter cover glass
- Removable metal grease filters, dishwasher safe
- Maximum extraction 629 m3/h
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 67 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Dimensions exhaust air (HxWxD): 750-1080 x 896 x 386 mm
- Dimensions recirculating (HxWxD): 862-1080 x 896 x 386 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Power rating: 216 W

* In accordance with the EU-Regulation No 65/2014

iQ100, Wall-mounted Extractor Hood, 90 cm, clear glass black printed LC95KA670

Dimensioned drawings

