





Powa-Prod 600W Pure Sine Wave 12V DC Inverter with Intelligent Charger & LCD Display - SA Socket AC Output

The Powa-Prod SO02-03 Pure Sine Wave Inverter is designed for increased backup-time power solutions for home or office appliances. In addition to the inverter function, the SO02-03 also contains a powerful intelligent multi-stage battery charger. The Pure Sine Wave output is suitable for any kind of loads. The ultra fast transfer time of less than 10ms makes it an ideal UPS solution for ITC equipment.

| | DC Input |
|-------------------------------|--|
| Nominal input voltage | 12 v |
| DC input voltage range | 10 - 15 v |
| | AC Input |
| Bypass voltage | 0 - 264 Vac for 220 / 230 / 240 Vac |
| AC voltage | 156 - 294 Vac |
| Nominal input frequency | 50 / 60 Hz ± 0.3 (auto-sensing) |
| | Output (AC Only) |
| DC mode output voltage | 220 / 230 / 240 Vac ± 5% |
| AC mode output voltage | 220 / 230 / 240 Vac ± 5% or 100 / 110/ 115/ 120 Vac ± 5% |
| Nominal output frequency | 50 / 60 Hz ± 0.3 (auto-sensing & settable) |
| Output waveform | Pure sine wave |
| Output power | 600 w |
| Efficiency | Max. 95% (mains mode); Max. 80% (inverter mode) |
| ECO mode | Settable (< 3% load) to enter in 80 s |
| No—load shutdown | Settable, time can be set (1 - 99 min), load can be set (3% - 50%) |
| Transfer time | less than 10 ms |
| Power factor | 1 |
| THD | less than 5% (linear load) |
| Inductive load | Yes |
| Motor load | Yes |
| Rectifier load | Yes |
| Overload capability | Mains mode: 110% for 120s, 125% for 60s, 150% for 10s (switch to bypass) |
| | Inverter mode: 110% for 60s, 125% for 10s, 150% for 10s (shut down) |
| | Battery |
| Charging current (selectable) | Max. 30 A |
| Equalizing charge voltage | Single battery 14.4 Vdc (default), 13.6 - 15 Vdc adjustable |
| Floating charge voltage | Single battery 13.7 Vdc (default), 13.2 - 14.6 Vdc adjustable |
| Charge mode | 3 stage charge mode |
| EOD | Single battery 10.2 Vdc (default), 9.6 - 11.5 Vdc adjustable |
| Reverse warning | Buzzer |
| | General |
| Interface | LCD & BUZZER |
| Operating temperature | 0°C - 40°C |
| Operating humidity | 5% - 95% RH |
| Forced air cooling | Variable speed fans |
| Net weight (kg) | 10.5 |
| Gross weight (kg) | 11.3 |
| Dimensions (W x D x H) (mm) | 400 x 210 x 127 |

