

# Series 6, Freestanding Fridge-freezer (Bottom freezer), glass door, 193 x 70 cm, Black, Total No Frost KGN56LB31U





NoFrost bottom freezer with 559 l gross capacity and VitaFresh plus freshness system, provides much more storage capacity for food, also keeps food up to two times longer fresh.

- VitaFresh: keeps food fresh for longer in climate controlled drawers at near  $0\,^{\circ}\text{C}.$
- Perfect Fit: place your fridge right next to walls or in a niche.
- Super Cooling function: cools new food placed inside faster, thus protecting already cooled food.
- Super Freezing function: Protects frozen food from defrosting.
- XXL capacity: extra space for your food when you need it.

Built-in / Free-standing:	Free-standing
Number of compressors:	1
Number of independent cooling systems:	2
Width of the appliance:	700 mm
Height:	1930 mm
Depth:	800 mm
Net weight:	105.5 kg
Door panel options:	Not possible
Door hinge:	. Right reversible
Number of Adjustable Shelves in fridge compartmen	t:3
Shelves for Bottles:	No
Frost free system:	Freezer
Interior ventilator:	No
Reversible Door Hinge:	Yes
Length electrical supply cord:	
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50 Hz
Storage Period in Event of Power Failure (h):	



Series 6, Freestanding Fridge-freezer (Bottom freezer), glass door, 193 x 70 cm, Black, Total No Frost KGN56LB31U

NoFrost bottom freezer with 559 l gross capacity and VitaFresh plus freshness system, provides much more storage capacity for food, also keeps food up to two times longer fresh.

## Consumption

- Energy efficiency class: A++
- Energy efficiency class: A++ (325 kWh per year). Actual energy consumption will depend on how the appliance is used and where it is located.
- Total net capacity: 505 litres
- Noise level dB(A) re 1 pW: 40

#### Design

- Doors Black, side panels Pearl grey (VZF 07127)
- Integrated Handle
- LED with Soft Start in fridge section

### **Comfort and Safety**

- Frost free never again defrosting
- Twin in-door LED electronic control
- Supercool function
- Superfreeze Function
- Optical and accoustic warning system
- Economy setting

## **Fridge Section**

- Net capacity refrigeration zone: 400 l
- Multi Airflow-System
- Air Fresh Filter
- 4 safety glass shelves of which 3 glass plates extendible
- 4 door bins, 1 dairy compartment4 door bins, there of 1x dairy compartment
- Pull-out tray with Breakfast box

## Freshness System

- VitaFresh plus: keeps food fresh for up to twice as long

## Freezer Section

- Net freezer capacity 105 litres
- Freezing capacity: 18 kg in 24 hours
- Storage time in power failure: 24 Hours
- 2 freezer drawers, incl. 1 Big Box

## **APPLIANCE DIMENSION**

- Dimensions: H 193 cm x L 70 cm x D 80 cm

## TECHNICAL INFORMATION

- Door right hinged, reversible
- Height adjustable front feet, roles in the back
- Climate Class SN-T
- Rated Voltage 220 240 V

### **Standard Accessories**

- 3 x egg tray, 1 x ice cube tray with lid, 1 x bottle holder in door tray

### **SPECIAL ACCESORIES**

### **Country Specific Options**

- Gross capacity, total: 559 l
- Gross capacity cooling 417 l
- \*\*\*\* freezer 142 l (-18°C and below)
- Based on the results of the standard 25-hour test. Actual consumption depends on usage/position of the appliance.

### **ENVIREMENT AND SAFETY**

### INSTALLATION

### **General Information**





# Series 6, Freestanding Fridge-freezer (Bottom freezer), glass door, 193 x 70 cm, Black, Total No Frost KGN56LB31U

( and a second s	Appliance name	а	b	С	d	е	f	g	h
Description  a Height  b Width  c Depth with door closed, without handle  d Cabinet depth  e Width with door opened to 90°  f Depth with door closed, with handle  g Depth with door closed, with handle	KGN56 (Inner handle)	1930	70	0 800	720	700	1450	800	12
a Height b Width c Depth with door closed, without handle d Cabinet depth e Width with door opened to 90° f Depth with door closed, with handle	KGN56 (Outer handle)	1930	70	0 800	720	740	1450	840	12
measurements is		a	a H b \ c [ d () e \ f [ g [	Height Vidth Depth with Cabinet de Vidth with Depth with Depth with	n door c epth i door o n door o	pened to pened losed, volument	o 90° with han recess o	dle r fitted (	

