



Flexible Expansion

Up to 50 units in parallel, 14.3kWh--716.8kWh capacity



No Black Out

Maximum discharge current: 200A, simultaneously supplying power to multiple loads



Ultra Safe

Intelligent fire extinguishing system, react within 5 seconds(optional)



Easy Installation

60% less volume, 25% less weight. Easy to move by one person with wheels



Long-term Reliability

LFP cells, long cycles, 10 years warranty



Smart Management

Real-time system monitoring, remote control, OTA updates

Model	PowerBrick
Battery Type	LiFePO₄
Nominal Battery Energy	14.336kWh
Nominal Voltage/Capacity	51.2V/28OAh
Recommended Charge/Discharge Current	140A (0.5C)
Max. Charge Current	200A
Max. Discharge Current	200A
Depth of Discharge	95%
Communication	CAN/RS485
Cycle Life *	Unlimited cycles / 10 Years
Protection Level	IP20
Net Weight	114kg
Dimension[W/D/H]	435/233/857mm (No wall -mounted bracket)
Maximum Parallel Modules	50
Charging Temp. Range	0~55°C
Discharging Temp. Range	-20~55°C
WIFI Module	Built-in WiFi module; APP OTA function
Fire Protection System	Optional Aerosol fire extinguisher
Certification & Safety Standard	UN38.3/CE-EMC/IEC62619/GOST-R
Compatible Inverters	SMA/Schneider/Victron energy/Ingeteam/Solis/GoodWe/Growatt/Soplanet/SOFAR/SAJ/DEYE etc.

^{*} Test conditions: 0.2C Charging & Discharging. @25°C, 95% DOD

