

AIR CURTAIN



- Aesthetically pleasing white finish, all-metal housing, advanced fire proof, easy installation and maintenance.
- Optimized air wheel with large air volume and low noise. Applied rigid fibreglass plastic air wheel, quality aluminum alloy fan wheel is optional for heavy oily smoke environment.
- Optimized motor operates 5000 hours continuously without any defects.
- Flexible control methods: switch control, remote control, magnetic sen-sor control

New Big Volume Air Curtain

Model	Specification (mm)	Rated Voltage [V]	Rated Frequency [HZ]	Installation Height (m)	Input Power (low/high/W)	Air Speed (m/s)	Air Volume (m ³ /h)	Noise (dB)	Dimension (mm)	Net Weight (kg)
SHFM-3509	900	110 ~ 220	50/60	3.0 - 3.5	115/135	11	2350	55	900x207x175	11.0
SHFM-3509Y	900	110 ~ 220	50/60	3.0 - 3.5	115/135	11	2350	55	900x207x175	11.0
SHFM-3512	1200	110 ~ 220	50/60	3.0 - 3.5	164/175	11	3050	57	1200x207x175	13.0
SHFM-3512Y	1200	110 ~ 220	50/60	3.0 - 3.5	164/175	11	3050	57	1200x207x175	13.0
SHFM-3515	1500	110 ~ 220	50/60	3.0 - 3.5	210/232	11	3950	59	1500x207x175	16.0
SHFM-3515Y	1500	110 ~ 220	50/60	3.0 - 3.5	210/232	11	3950	59	1500x207x175	16.0